

**Transmission Fluid****PETRONAS Tutela Multi ATF 500****Range:**

**Long description:** DEXRON®-VI approved, multi-vehicle Automatic Transmission Fluid, delivering long-lasting shifting performance and component durability. Suitable up to 6 speed automatic transmissions Meets the requirement of JASO M315-2013 1A and JASO M315-2013 2A. It is also suitable for use in power steering and hydraulic systems of passenger cars requiring GM DEXRON®-VI/Ford MERCON® and previous level of performances

[Product data sheet](#) [Safety data sheet](#)

**Industry Specifications:** JASO M315-2013 1A, JASO M315-2013 2A Allison C-4

**OEM Approvals - Only for Automotive:** GM DEXRON®-VI

**OEM Performance - Only for Automotive:** Aisin Warner JWS 3309, JWS 3314, JWS 3317, JWS 3324, AW-1 ATF RED 1/ RED 1K BMW LA2634, LT71141, 7045E, ETL-8072B, MINI T-VI Bosch TE-ML 09 Daewoo LT 71141 Daihatsu AMMIX ATF D-II, Daihatsu AMMIX ATF D-III SP Chrysler/Jeep ATF+3/ATF +4, NAG 1 Ford MERCON®, Ford FNRS, Ford XT-2-QDX (M), XT-2-QSM (Syn), WSS M2C138CJ, WSS M2C166H, WSS M2C 922A1, WSS M2C 924A (XT-8-QAW) JWS 3309, ESP-M2C166H, XL-12 FUSO ATF-II/ATF-SP III/ATF A4 GM DEXRON® IIIH Hino Blue Ribbon ATF Honda ATF Z1 (except CVT), DW-1 Hyundai/Kia SP-II, SP-III, SP-IV ISUZU BESCO ATF-II, ATF-III, ATF-SP, SCS Fluid Mazda ATF D-II/ATF M-III/ATF M-V/ATF F-1/ATF S-1/ATF N-1/ATF-3317 Mitsubishi Diaqueen SK/SP-II/SP-III/J2/J3/ATF PA/SP-IV/AW Nissan Matic Fluid C/D/J/K/S Peugeot/Citroen (PSA) AL4 Porsche LT71141, ATF 3403-M115, JWS 3309 Renault Matic D2/DPO/AL4, SATF-D SSang yong DSIH 5M-66 Subaru ATF/ATF HP/ATF 5AT/ATF AW-1 Suzuki ATF AW-1/AT OIL 5D06/ATF 2384K/ATF 3314/ATF 3317/JWS 3309 Toyota ATF D-II/D-III/T-IV, ATF WS Audi/Seat/Skoda/VW G 052 025, G 052 162, G 052 990, G 055 025, G 053 025, G 055 540, G 052 055 ZF 3, 4 and 5 speed transmissions

**Application(s) - For Consumers pages:** Light-duty Commercial Vehicle (LCV), Passenger car