

## Engine Oil



### PETRONAS Urania 5000 LSF 5W-30

Range: PETRONAS Urania 5000

**Long description:** PETRONAS Urania 5000 LSF 5W-30 is a fully synthetic fuel efficient low SAPS extended drain CK-4/E6 engine oil suitable suitable for Euro VI and Euro V heavy duty diesel applications including modern, high-output, low emission engines fitted with latest emission control systems. It is also suitable for older turbocharged and naturally aspirated diesel engines, both on-highway and off-highway. Suitable for CNG and LNG vehicles where this performance profile is need. It helps in extending engine life and reduces the total cost of ownership. Approved by most important Trucks and Bus manufacturers.

[Product data sheet](#) [Safety data sheet](#)

Viscosity: 5W-30

Industry Specifications: API CK-4, API CJ-4, API SN ACEA E6, E7, E9 JASO DH-2

OEM Approvals - Only for Automotive: Cummins CES 20086 Deutz DQC IV-18 LA Mack EOS-4.5 MAN M3677 MB-Approval 228.51 MTU CAT. 3.1 Renault RLD-3 Scania LDF-4 Volvo VDS-4.5

OEM Performance - Only for Automotive: CAT ECF-3 Cummins CES 20081 Detroit Diesel DFS93K222/218 DAF Extended Drain\* (DAF Rapido Service system required) Ford WSS-M2C213-A MAN M3477 Scania Low Ash Volvo VDS-4

Application(s) - For Consumers pages: Heavy-Duty Vehicle (HD)

Sector(s) - For Businesses page: Road Transport