

Engine Oil**PETRONAS Urania 5000 E 5W-30**

Range: PETRONAS Urania 5000

Long description: PETRONAS Urania 5000 E 5W-30 is a low SAPS oil that is suitable for Euro VI and Euro V heavy duty diesel applications including modern, high-output, low emission engines fitted with emission control systems using DPF, SCR, DOC and EGR technologies. It is also suitable for older turbocharged and naturally aspirated diesel engine generations, both on-highway and off-highway, running on high or ultra-low Sulphur diesel and bio-diesel. Suitable for all OEMs requiring CNG for transportation.

 [Product data sheet](#)  [Safety data sheet](#)

Viscosity: 5W-30

Industry Specifications: API CJ-4 ACEA E6, E7, E9

OEM Approvals - **Only for Automotive:** Deutz DQC IV-10 LA MAN M3677 MB-Approval 228.51 MTU CAT. 3.1 Renault RLD-3 Scania LDF-4

OEM Performance - **Only for Automotive:** CAT ECF-3 Cummins CES 20081 Detroit Diesel DFS93K218 DAF Extended Drain* (DAF Rapido Service system required) MAN M3477 MAN M3575 / M3271-1 Mack EO-O Premium Plus Volvo VDS-4

Application(s) - **For Consumers pages:** Heavy-Duty Vehicle (HD)

Sector(s) - **For Businesses page:** Road Transport