

Coolant



PETRONAS Tutela Coolant LL-G Premix

Range:

Long description: PETRONAS Tutela Coolant LL-G Premix is a premium performance ready to use Long-Life Coolant delivering optimized performance and component durability for vehicles cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Hybrid Organic Acid inhibitor, silicates and phosphates (HOAT Technology), free of nitrites and amines, it provides excellent protection against overheating, frost and corrosion.

[Product data sheet](#) [Safety data sheet](#)

Industry Specifications: AFNOR NF R 15-601 AS 2108-2004 ASTM D 3306 ASTM D 4985 ASTM D 6210 BS 6580:2010 CUNA NC 956-16 JIS K 2234:2006 ONORM V 5123 SAE J1034 SANS 1251:2005

OEM Performance - Only for Automotive: BMW N 600 69.0 Bez. Reg. Amsberg, Dept. Of Mining and Energy 84.12.22.63-2001-2 Daimler/Mercedes-Bens 325.0 Deutz H-LV 0161 0188 German Army TL 6850-0038/1 Jenbacher TA-Nr. 1000-0201 Liebherr Machines Bulle TVL 035 / TVL 23009 A MAN 324-NF MTU MTL 5048 Opel/General Motors B 040 0240 Porsche for 924, 928, 944, 968 Saab 6901599 VW / Audi / Seat / Skoda TL 774-C

Application(s) - For Consumers pages: Passenger car

Sector(s) - For Businesses page: Road Transport